

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

AD-A265 104



average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, completing and reviewing the collection of information, Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington, DC 20503, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Project (0704-0188), Washington, DC 20503.

REPORT DATE

April 1993

3. REPORT TYPE AND DATES COVERED

professional paper

4. TITLE AND SUBTITLE

RECENT MAN-MADE RADIO NOISE MEASUREMENTS

5. FUNDING NUMBERS

PR: CN21

PE: N/A

WU: DN309072

6. AUTHOR(S)

D. B. Sailors

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

Naval Command, Control and Ocean Surveillance Center (NCCOSC)
RDT&E Division
San Diego, CA 92152-5001

8. PERFORMING ORGANIZATION
REPORT NUMBER

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)

Space and Naval Warfare Systems Command
Washington, DC 20363-5100

10. SPONSORING/MONITORING
AGENCY REPORT NUMBER

11. SUPPLEMENTARY NOTES

12a. DISTRIBUTION/AVAILABILITY STATEMENT

Approved for public release; distribution is unlimited.

12b. DISTRIBUTION CODE

13. ABSTRACT (Maximum 200 words)

Comparison of man-made noise models against recently acquired man-made noise data measured on circular disposed antenna arrays (CDAA) at the receive sites of communication stations at Adak, AL; Diego Garcia; Guam, Honolulu, HI; San Diego, CA; and Stockton, CA is reported. These measurements were made by the Naval Electronics Engineering Activity, Pacific (NEEAP) on their Automated Noise Measurement System (ANMS). Baseline noise data were provided by NEEAP for the forenamed sites measured by the ANMS for the local noon period. Local noon was chosen as the most likely time of day man-made noise would most likely be present.

The data for Guam was compared to other measured results (Shepherd et al., "MF and HF Man-made Radio-Noise and Interference Survey—Guam," Final Report, SIR Project 3328, Stanford Research Institute, 1974). There was a large difference between these two measurements partially due to the measurements by NEEAP being made on a CDAA type antenna rather than on a standard short vertical rod. Using conversion factors obtained by Hagn in Iceland (Hagn, G. H., "Calibration of Nine-foot Rod Antenna for MF and HF EMC Measurements and Comparison with AN/FRD-10 Antenna; Volume I: Groundwave," Final Report, SRI Project 6972, Stanford Research Institute, 1978), the noise data was converted to that of a nine foot vertical rod. The results of this conversion are presented along with curves for rural, quiet rural, and galactic noise.

93-12099



93 5 27 09 4

Published in *National Radio Science Meeting Abstracts*, 7-10 January 1992, p. 245.

14. SUBJECT TERMS

communications
networks

HF Communication

15. NUMBER OF PAGES

16. PRICE CODE

17. SECURITY CLASSIFICATION
OF REPORT

UNCLASSIFIED

18. SECURITY CLASSIFICATION
OF THIS PAGE

UNCLASSIFIED

19. SECURITY CLASSIFICATION
OF ABSTRACT

UNCLASSIFIED

20. LIMITATION OF ABSTRACT

SAME AS REPORT

UNCLASSIFIED

21a. NAME OF RESPONSIBLE INDIVIDUAL

D. B. Sailors

21b. TELEPHONE (include Area Code)

(619) 553-3063

21c. OFFICE SYMBOL

Code 542

E3-2 RECENT MAN-MADE RADIO NOISE MEASUREMENTS
 1400 David B. Sailors
 Ocean and Atmospheric Sciences Division
 Naval Ocean Systems Center
 San Diego, CA 92152-5000

Comparison of man-made noise models against recently acquired man-made noise data measured on circular disposed antenna arrays (CDAA) at the receive sites of communication stations at Adak, AL; Diego Garcia; Guam; Honolulu, HI; San Diego, CA; and Stockton, CA is reported. These measurements were made by the Naval Electronics Engineering Activity, Pacific (NEEAP) on their Automated Noise Measurement System (ANMS). Baseline noise data were provided by NEEAP for the forenamed sites measured by the ANMS for the local noon period. Local noon was chosen as the most likely time of day man-made noise would most likely be present.

The data for Guam was compared to other measured results (Shepherd et al., "MF and HF Man-made Radio-Noise and Interference Survey—Guam," Final Report, SRI Project 3328, Stanford Research Institute, 1974). There was a large difference between these two measurements partially due to the measurements by NEEAP being made on a CDAA type antenna rather than on a standard short vertical rod. Using conversion factors obtained by Hagn in Iceland (Hagn, G.H., "Calibration of Nine-foot Rod Antenna for MF and HF EMC Measurements and Comparison with AN/FRD-10 Antenna; Volume I: Groundwave," Final Report, SRI Project 6792, Stanford Research Institute, 1978), the noise data was converted to that of a nine foot vertical rod. The results of this conversion are presented along with curves for rural, quiet rural, and galactic noise.

DTIC QUALITY INSPECTED

Accession For	
NTIS CRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
A-1	20